



SEALS and CYLINDERS



MCVR84 Cover Seals

- Urethane cover seals are designed to replace O-rings for most hydraulic applications
- Eliminates common problems such as twisting and tearing as well as the need for a backup ring at high pressures
- Also may be used as a double acting seal in many hydraulic applications previously using a conventional O-ring to provide better wear characteristics and greater resistance to extrusion.



MWRE SC Wear Rings

- Molded from glass fiber reinforced polyetherimide-a high strength and heat resistant material
- OD surface features diagonal grooves which serve to retain fluid for added lubrication
- Wear rings are commonly used within Caterpillar, John Deere, and Hitachi cylinders.



Bobcat Replacement Cylinders

- Net price - Up to 50% off OEM price!
- 18 month warranty* vs OEM 12 month warranty
- Made in the USA
- In-stock, same day shipment
- Reduce customer downtime by replacing versus repairing cylinders
- Upgrade - Rod seal to Freudenberg-NOK AU30000 high performance material rated for 250°F and up to 7250psi; resulting in extended seal life.
- Upgrade - Cast iron gland with buttress threads vs aluminum OEM gland means less galled or damaged threads
- Upgrade - Induction hardened chrome rod which is less susceptible to bending
- In-stock Hercules Bobcat seal kits available

KITS


Vickers Eaton NZ Kits



Sheffer MH Series Kits

Kit Includes:

- 1 Urethane Rod Wiper
- 1 Urethane Rod Seal
- 1 NBR Gland O-ring
- 1 PTFE Piston seal
- 1 Piston Wear Strip
- 1 NBR Piston/ Rod O-ring
- 2 NBR Tube End O-rings



Genie Equipment Kits

- Complete repair kits per OEM specifications
- Exceed or meet OEM quality
- Seal kits for both rotators and cylinders



Enerpac® Equipment Kits

- Provide the same high quality components found in OEM kits at the right price!
- In stock for immediate delivery

Filters and Tools



High Pressure Spin-On Filters

Hercules high pressure spin-on filters are interchangeable with Donaldson Duramax® HMK04 and HMK05 series.



Piston Seal Stretcher

- 8 stepped segments
- 1 top nut/handle
- 5/16" thick aluminum flat base with 4 bolt holes to anchor to work bench
- 1 threaded rod with a piston pre-installed
- 1 stop adjustable nut